

AHD DOME CAMERA



Features		LAD3200R	LAV3200R
Camera	Image Sensor	6.23 mm (1/2.9 Type) CMOS	6.23 mm (1/2.9 Type) CMOS
	Lens	4 mm F2.1	2.8 ~ 12 mm F1.4
	Min. Illumination	0 lux @ IR LED on	0 lux @ IR LED on
	Day / Night	ICR (Auto)	ICR (Auto)
	WDR	Digital (Automatic Tone Control)	Digital (Automatic Tone Control)
	Electronic Shutter	Auto	Auto
	3D-DNR	Auto	Auto
	Gain Control	Auto	Auto
	IR LEDs	24	28
	IR Distance	20 m	30 m
Focus	Manual	Manual	
Video	Video Format	AHD	AHD
	Max. Frame Rate	30 fps @ 1920 x 1080 (NTSC) 25 fps @ 1920 x 1080 (PAL)	30 fps @ 1920 x 1080 (NTSC) 25 fps @ 1920 x 1080 (PAL)
	Synchronization	Internal	Internal
	Max. Transmission Distance	500 m (75Ω - 5C)	500 m (75Ω - 5C)
	Interface	BNC	BNC
General	Power Source	DC12 V	DC12 V
	Max. Power Consumption	4.2 W	4.2 W
	Operating Temperature / Humidity	-10 °C ~ 55 °C / 0 % ~ 80 % RH	-10 °C ~ 55 °C / 0 % ~ 80 % RH
	Standard Approvals	FCC, CE, KC, VCCI, Police (China)	FCC, CE, KC, VCCI, Police (China)
	Color / Material	White / Diecasting	White / Diecasting
	Ingress Protection	IP66	IK10, IP66
	Dimension (Ø x H)	Ø93 x 68 mm	Ø147 x 112 mm
Weight	330 g	820 g	

※ Exact products and specifications shown may vary by geographic region and are subject to change without notice. Actual products may differ from the images appearing in the catalog.