



## BOX CAMERA

Model		RNOE-B501A
Camera	Image Sensor	CMOS
	Mount Type	C/CS
	Min. Illumination	Color: 0.04 lux (F1.2,AGC ON), B/W: 0.004 lux (F1.2,AGC ON)
	Day / Night	Dual ICR
	Focus	ABF
	Image Setting	Configurable Brightness, Saturation, Contrast, HLC, Smart Defog, Corridor, EIS
	Video/Audio	Video Compression
Resolution		60Hz: 1080p@30fps, 960p@30fps, 720p@60fps 50Hz: 1080p@25fps, 960p@25fps, 720p@50fps
Max. Frame Rate		1280 x 720@60fps
Multi-Streaming		3
ROI (Region of Interest)		4 zones
Privacy Mask		Yes (Up to 4)
Motion Detection		Yes
Video Analytics		Tripwire / Perimeter / Missing & Foreign object / Crowd / Loitering / Fast Moving / Parking / Audio Offline
Streaming on Motion		Yes
Text Overlay		Yes
Audio Compression		G.711A / G.711U / ADPCM / AAC
Two-way Audio		Yes
Audio Detection		Yes
Event		Event Trigger
	Event Notification	Relay out, Email, FTP
	Pre/Post Event Buffering	Yes
Interface	Analog Video Out	1 BNC Out
	Audio In / Out	1 In / 1 Out
	Alarm In / Out	2 In / 1 Out
	RS-485	Yes
	Storage	SD (Up to 128 GB)
Network	Ethernet	RJ-45 10/100BASE-T
	Security	Password protection, IP filter
	Open Protocol	ONVIF (Profile S)
	Protocol	IPv4 / IPv6, HTTP, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, TCP, UDP, DHCP, PPPoE
	Web Viewer	IE8, IE10, IE11, Chrome42 under version, Firefox3.5+
	Video Management Software	Mobile App (iPhone, iPad, Android)
	Max. Connections	4 Level / 8 Users
General	Power Source	DC12V, AC24V, POE
	Max. Power Consumption	6.7W
	Max. Input Current	500mA(AC24V), 500mA(DC12V), 150mA(POE)
	Operating Temperature / Humidity	-35°C ~ 65°C / 0% ~ 95%RH
	Standard Approvals	KC, LVD, CE
	Language	Korean, Chinese, Japanese, English, Turkish, Spanish
	Color / Material	Black & White / Diecasting
	Dimension (W x H x D)	158.3mm x 64mm x 76mm
Weight	0.9kg (Camera Only)	

※ Exact products and specifications shown may vary by geographic region and are subject to change without notice. Actual products may differ from the images appearing in the catalog.