



PTZ CAMERA

Model	RNZE-B501A	
Camera	Image Sensor	CMOS
	Lens	x33 (4.6-152mm)
	Min. Illumination	Color: 0.03 lux @ F1.6 (AGC ON), B/W: 0 lux @ IR LED on
	Day / Night	Dual ICR
	IR Distance	150m
	Image Setting	Configurable Brightness, Saturation, Contrast, HLC, Smart Defog, EIS
PTZ	Optical Zoom	x33
	Panning Range & Speed	0° ~ 360°, Max. 240°/sec
	Tilting Range & Speed	-16° ~ 90°, Max. 180°/sec
	Auto Panning	Mac. 8 scans
	Preset/ID	500
	Group touring / Pattern	8 / 8
Video/Audio	Video Compression	H.265, H.264 HP / MP / BP, M-JPEG
	Resolution	60Hz: 1080p@30fps, 960p@30fps, 720p@60fps 50Hz: 1080p@25fps, 960p@25fps, 720p@50fps
	Max. Frame Rate	60fps@1280x720
	Multi-Streaming	3
	ROI (Region of Interest)	4 zones
	Privacy Mask / Motion Detection	Yes (Up to 4) / Yes
	Video Analytics	Tripwire / Perimeter / Missing & Foreign object / Crowd / Loitering / Fast Moving / Parking / Audio Offline
	Text Overlay	Yes
	Audio Compression	G.711A / G.711U / ADPCM / AAC
	Two-way Audio	Yes
Event	Event Trigger	Motion detection, IP Conflict, Port Alarm
	Event Notification	Relay out, Email, FTP, Go to Preset
	Pre/Post Event Buffering	Yes
Interface	Audio In / Out	1 In / 1 Out
	Alarm In / Out	1 In / 1 Out
	Storage	Micro SD (Up to 128 GB)
Network	Ethernet	RJ-45 10/100BASE-T
	Security	Password protection, IP filter
	Open Protocol	ONVIF (Profile S)
	Protocol	IPv4 / IPv6, HTTP, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, TCP, UDP, DHCP, PPPoE
	Web Viewer	IE8, IE10, IE11, Chrome42 under version, Firefox3.5+
	Video Management Software	Mobile App (iPhone, iPad, Android)
	Max. Connections	4 Level / 8 Users
	Power Source	AC24V
General	Max. Power Consumption	27W (2200mA)
	Operating Temperature / Humidity	-40° C ~ 60° C / 0% ~ 95%RH
	Standard Approvals	KC, LVD, CE
	Language	Japanese, Korean, Chinese, English, Turkish, Spanish
	Color / Material	White, Black / Diecasting
	Ingress Protection	IP66
	Dimension (Ø x H)	223mm x 372 mm
	Weight	5.1 kg (Camera Only)

※ Exact products and specifications shown may vary by geographic region and are subject to change without notice. Actual products may differ from the images appearing in the catalog.